MHN33PR **ENERGY ADVANTAGE™** FRONT-LOAD WASHER





- Delivers more accurate cycle times and better unbalanced performance*
- dampers and two springs, providing better stability for the entire wash unit.
- reading of cabinet vibration.

DURACORE DRIVE SYSTEM

- DuraCore Drive System is designed and tested to run 15,000 cycles.**
- Watertight, flexible triple-lip seal with garter spring keeps moisture away from the shaft, protecting the premium bearings.
- Durable shaft sleeve is designed to eliminate shaft wear.

INTELLIGENT CONTROLS WITH M-SERIES TECHNOLOGY

- Provides powerful profits for owners and flexibility for customers.
- Enhanced controls allow customized setup; each cycle and option can be priced individually, maximizing revenue.

ENERGY-EFFICIENT CLEANING

- ENERGY STAR®-certified and uses on average 10.71 gallons of water per cycle, which helps reduce energy and water costs.
- TurboWash™ System's proven high-efficiency technology delivers energy savings without sacrificing cleaning performance.

CLOTHESPIN™ APP BY MAYTAG COMPATIBLE

- · Customers will love how convenient it is to do their laundry with the new Clothespin™ app by Maytag.
- They can use their smartphones to pay for their laundry, remotely check for available washers and dryers, and receive a notification when their laundry cycles are complete ***
- *Compared to previous model, MHN30, based on 18-lb. load.
- **Based on 11-lb. load, 34 min. timed cycle, Heavy Soil.
- ***Subject to terms of use and privacy policy. Message and data rates may apply. In Canada, Maytag Connect 360° compatible only.


































OUR COMMITMENT TO DEPENDABLE QUALITYFor well over 50 years, Maytag® Commercial Laundry has promised and delivered dependability. We create that quality by making durable washers and dryers, built to endure heavy use and last for years. We design our machines to perform reliably and to produce consistent results. Finally, we give our washers and dryers the power to do their jobs thoroughly, cleaning and drying laundry quickly and efficiently—and justifying the trust that has been placed in us for generations.

MAYTAG® ENERGY ADVANTAGE™ HE FRONT-LOAD WASHER INTELLIGENT CONTROLS. CARD READER

MODEL MOTOR	WASHER SPECIFICATIONS	CONTROL CONTRO
Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction Yes Wash—HP (kw) .09 (07) Extract—HP (kw) .54 (40) Average energy consumption per cycle (kWh) .054 CAPACITY .054 Cylinder volume—cu. ft. (liters) 3.1 (88) Cylinder depth—in. (mm) 21.6 (547) Cylinder depth—in. (mm) 13.4 (341) WATER INLET HOSE	MODEL	MHN33PR
high-efficiency, controlled induction	MOTOR	
Extract—HP (kw)		Yes
Average energy consumption per cycle (kWh) CAPACITY Cylinder volume—cu. ft. (liters) Cylinder diameter—in. (mm) Cylinder depth—in. (mm) 21.6 (547) Cylinder depth—in. (mm) 3.1 (341) WATER INLET HOSE Ft. (m) APPROXIMATE WATER USAGE—GALLONS (LITERS) Average hot water usage, hot water cycle Average hot water usage, hot water cycle Average hot water usage per cycle Modified Energy Factor (MEF) CLEGTRICAL RATINS Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps WASH SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) Depth—in. (mm) Dore pering diameter—in. (mm) 14.25 (362) DPTIONAL PEDESTAL ADD:	Wash-HP (kw)	.09 (.07)
CAPACITY Cylinder volume—cu. ft. (liters) Cylinder diameter—in. (mm) 21.6 (547) Cylinder depth—in. (mm) MATER INLET HOSE Ft. (m) BRAIN HOSE Ft. (m) APPROXIMATE WATER USAGE—GALLONS (LITERS) Average hot water usage, hot water cycle Average hot water usage, warm water cycle Average total water usage per cycle 10.71 (40.5)* Modified Energy Factor (MEF) ELECTRICAL RATING Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps 15 WASH SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE 1,000/300 WATER SUPPLY PRESSURE PSI (bar) ADJUSTABLE LEVELING LEGS COLOR White APPROXIMATE WEIGHT Crated—lbs. (kg) DIMENSIONS Width—in. (mm) Door opening diameter—in. (mm) DOOR OPTIONAL PEDESTAL ADD:	, ,	.54 (.40)
Cylinder volume—cu. ft. (liters) 3.1 (88) Cylinder diameter—in. (mm) 21.6 (547) Cylinder depth—in. (mm) 13.4 (341) WATER INLET HOSE Ft. (m) 4 (1.22) DRAIN HOSE Ft. (m) 6 (1.83) APPROXIMATE WATER USAGE—GALLONS (LITERS) Average hot water usage, hot water cycle 2.71 (10.26) Average hot water usage, warm water cycle 71 (2.69) Average total water usage per cycle 10.71 (40.5)* Modified Energy Factor (MEF) 2.45 Water Factor (WF) 3.50 ELECTRICAL RATING 120V/60Hz Domestic model—voltage 120V/60Hz BREAKER/FUSE MIN. REQUIREMENTS 15 Domestic model—woltage 15 EXTRACT SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE 1,000/300 WATER SUPPLY PRESSURE 9si (bar) Psi (bar) 20-100 (1-8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Uncrated—lbs. (kg) 235 (107) DIMENSIONS 27	Average energy consumption per cycle (kWh)	.054
Cylinder diameter—in. (mm) 21.6 (547) Cylinder depth—in. (mm) 13.4 (341) WATER INLET HOSE Ft. (m) 4 (1.22) DRAIN HOSE Ft. (m) 6 (1.83) APPROXIMATE WATER USAGE—GALLONS (LITERS) Average hot water usage, hot water cycle 2.71 (10.26) Average hot water usage, warm water cycle 71 (2.69) Average total water usage per cycle 10.71 (40.5)* Modified Energy Factor (MEF) 2.45 Water Factor (WF) 3.50 ELECTRICAL RATING 120V/60Hz Domestic model—voltage 120V/60Hz BREAKER/FUSE MIN. REQUIREMENTS 15 Domestic model—amps 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE 1,000/300 WATER SUPPLY PRESSURE 1,000/300 Psi (bar) 20-100 (1-8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Uncrated—lbs. (kg) 235 (107) DIMENSIONS Width—in. (mm) 27 (686) Depth—in.	CAPACITY	
Cylinder depth—in. (mm)	Cylinder volume—cu. ft. (liters)	3.1 (88)
### WATER INLET HOSE Ft. (m)	Cylinder diameter—in. (mm)	21.6 (547)
Ft. (m)	Cylinder depth—in. (mm)	13.4 (341)
DRAIN HOSE	WATER INLET HOSE	
Ft. (m)	Ft. (m)	4 (1.22)
APPROXIMATE WATER USAGE—GALLONS (LITERS) Average hot water usage, hot water cycle Average hot water usage, warm water cycle Average total water usage per cycle Average total water usage per cycle Modified Energy Factor (MEF) ELECTRICAL RATING Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps 15 WASH SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) Dimensions Width—in. (mm) Depth—in. (mm) includes handle Height—in. (mm) Door opening diameter—in. (mm) DPTIONAL PEDESTAL ADD:	DRAIN HOSE	
Average hot water usage, hot water cycle Average hot water usage, warm water cycle Average total water usage per cycle Average total water usage per cycle Modified Energy Factor (MEF) 2.45 Water Factor (WF) ELECTRICAL RATING Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps 15 WASH SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) Dimensions Width—in. (mm) Depth—in. (mm) includes handle POTIONAL PEDESTAL ADD: DITIONAL PEDESTAL ADD:	Ft. (m)	6 (1.83)
Average hot water usage, warm water cycle Average total water usage per cycle 10.71 (40.5)* Modified Energy Factor (MEF) 2.45 Water Factor (WF) 3.50 ELECTRICAL RATING Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps 15 WASH SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) DIMENSIONS Width—in. (mm) Depth—in. (mm) includes handle POTIONAL PEDESTAL ADD: 10.71 (2.69) 10.71 (40.5)* 10.71	APPROXIMATE WATER USAGE-GALLONS (LITERS)	
Average total water usage per cycle Modified Energy Factor (MEF) Vater Factor (WF) ELECTRICAL RATING Domestic model—voltage BREAKER/FUSE MIN. REQUIREMENTS Domestic model—amps 15 WASH SPEED—RPM EXTRACT SPEED—MAX RPM/MAX G-FORCE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) DIMENSIONS Width—in. (mm) Depth—in. (mm) includes handle Door opening diameter—in. (mm) DOTIONAL PEDESTAL ADD:	Average hot water usage, hot water cycle	2.71 (10.26)
Modified Energy Factor (MEF) 2.45	Average hot water usage, warm water cycle	.71 (2.69)
Water Factor (WF) 3.50 ELECTRICAL RATING 120V/60Hz Domestic model—voltage 120V/60Hz BREAKER/FUSE MIN. REQUIREMENTS 15 Domestic model—amps 40 EXTRACT SPEED—RPM 40 EXTRACT SPEED—MAX RPM/MAX G-FORCE 1,000/300 WATER SUPPLY PRESSURE 20-100 (1-8) Psi (bar) 20-100 (1-8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Uncrated—lbs. (kg) 235 (107) DIMENSIONS Vidth—in. (mm) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD: ************************************	Average total water usage per cycle	10.71 (40.5)*
Domestic model—voltage	Modified Energy Factor (MEF)	2.45
Domestic model—voltage	Water Factor (WF)	3.50
Domestic model—amps 15	ELECTRICAL RATING	
Domestic model—amps	Domestic model—voltage	120V/60Hz
WASH SPEED-RPM 40 EXTRACT SPEED-MAX RPM/MAX G-FORCE 1,000/300 WATER SUPPLY PRESSURE 20-100 (1-8) Psi (bar) 20-100 (1-8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Crated—lbs. (kg) 235 (107) DIMENSIONS Vidth—in. (mm) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	**	
EXTRACT SPEED—MAX RPM/MAX G-FORCE WATER SUPPLY PRESSURE Psi (bar) ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) 235 (107) DIMENSIONS Width—in. (mm) Depth—in. (mm) includes handle Height—in. (mm) Door opening diameter—in. (mm) DOTIONAL PEDESTAL ADD:	Domestic model—amps	15
WATER SUPPLY PRESSURE Psi (bar) 20–100 (1–8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Crated—lbs. (kg) 235 (107) DIMENSIONS 27 (686) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	WASH SPEED-RPM	40
Psi (bar) 20–100 (1–8) ADJUSTABLE LEVELING LEGS Yes COLOR White APPROXIMATE WEIGHT 244 (111) Crated—lbs. (kg) 235 (107) DIMENSIONS Vidth—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	EXTRACT SPEED—MAX RPM/MAX G-FORCE	1,000/300
ADJUSTABLE LEVELING LEGS COLOR APPROXIMATE WEIGHT Crated—lbs. (kg) Uncrated—lbs. (kg) 235 (107) DIMENSIONS Width—in. (mm) Depth—in. (mm) includes handle Height—in. (mm) Door opening diameter—in. (mm) DOTIONAL PEDESTAL ADD:	WATER SUPPLY PRESSURE	
COLOR White APPROXIMATE WEIGHT 244 (111) Crated—lbs. (kg) 235 (107) DIMENSIONS 27 (686) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	Psi (bar)	20-100 (1-8)
APPROXIMATE WEIGHT Crated—lbs. (kg) 244 (111) Uncrated—lbs. (kg) 235 (107) DIMENSIONS Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	ADJUSTABLE LEVELING LEGS	Yes
Crated—lbs. (kg) 244 (111) Uncrated—lbs. (kg) 235 (107) DIMENSIONS 27 (686) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	COLOR	White
Uncrated—lbs. (kg) 235 (107) DIMENSIONS Width—in. (mm) Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	APPROXIMATE WEIGHT	
DIMENSIONS Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	Crated—lbs. (kg)	244 (111)
Width—in. (mm) 27 (686) Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	Uncrated—lbs. (kg)	235 (107)
Depth—in. (mm) includes handle 28.81 (732) Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	DIMENSIONS	
Height—in. (mm) 37.81 (961) Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	Width—in. (mm)	27 (686)
Door opening diameter—in. (mm) 14.25 (362) OPTIONAL PEDESTAL ADD:	Depth—in. (mm) includes handle	28.81 (732)
OPTIONAL PEDESTAL ADD:		37.81 (961)
		14.25 (362)
Height—in. (mm) 2.75 (70)	OPTIONAL PEDESTAL ADD:	
	Height—in. (mm)	2.75 (70)

^{*}Average based on DOE J1 testing with factory preset cycles. Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.



ENERGY ADVANTAGE™

